

# MATERIAL SAFETY DATA SHEET



**Date Issued:** 09/07/2006  
**MSDS No:** ST-1085 PART A  
**Date-Revised:** 09/07/2006  
**Revision No:** New MSDS

## ST-1085 PART A

### 1. PRODUCT AND COMPANY IDENTIFICATION

**PRODUCT NAME:** ST-1085 PART A  
**GENERAL USE:** Polyurethane resin  
**CHEMICAL FAMILY:** Diisocyanate terminated polyglycols in plasticizer/paraffin mixture

#### MANUFACTURER

BJB Enterprises, Inc.  
 14791 Franklin Avenue  
 Tustin, CA 92780  
**Customer Service Number:** (714) 734-8450  
**Fax:** (714) 734-8929

#### 24 HR. EMERGENCY TELEPHONE NUMBERS

**CHEMTREC (US Transportation):** (800) 424-9300  
 or (703) 527-3887

### 2. HAZARDS IDENTIFICATION

#### EMERGENCY OVERVIEW

**PHYSICAL APPEARANCE:** Pale yellow viscous liquid with a slight aromatic hydrocarbon odor.

**IMMEDIATE CONCERNS:** May cause eye and skin irritation. Use in well ventilated areas. Avoid breathing vapors. Avoid contact with strong oxidizers and strong acids, as sudden reaction may result in fire and toxic fumes. Reacts slowly with water to produce carbon dioxide which may rupture containers. This reaction accelerates at higher temperatures.

#### POTENTIAL HEALTH EFFECTS

**EYES:** May cause irritation, tearing, reddening, and swelling.

**SKIN:** May cause irritation and possible allergic sensitivity. Skin inflammation is characterized by itching, scaling, or reddening.

**INGESTION:** May be harmful if swallowed.

**INHALATION:** May be harmful if inhaled. Inhalation at levels above the occupational exposure limit could cause respiratory sensitization and risk of serious damage to the respiratory system. The onset of the respiratory symptoms may be delayed for several hours after exposure. A hyper-reactive response to even minimal concentrations of diisocyanates may develop in sensitized persons.

**MEDICAL CONDITIONS AGGRAVATED:** May cause or aggravate dermatitis and asthma.

**ROUTES OF ENTRY:** Eye and skin contact, inhalation of vapors, or accidental ingestion.

### 3. COMPOSITION / INFORMATION ON INGREDIENTS

<u>Chemical Name</u>	<u>Wt. %</u>	<u>CAS</u>
Polytetramethylene glycol polymer 1,3 diisocyanatomethylbenzene terminated	40 - 60	Proprietary
Polypropylene glycol polymer 1,3 diisocyanatomethylbenzene terminated	20 - 40	Proprietary
Chlorinated paraffins	5 - 10	063449-39-8
Dibutyl phthalate	1 - 5	000084-74-2
Aromatic hydrocarbon	< 2	064742-94-5
Naphthalene	< 0.2	000091-20-3
Toluene-2,6-diisocyanate	< 0.035	000091-08-7
Toluene-2,4-diisocyanate	< 0.03	000584-84-9

### 4. FIRST AID MEASURES

**EYES:** Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Have eyes examined and tested by medical personnel.

**SKIN:** Immediately wash skin with soap and plenty of water. Remove contaminated clothing. Get medical attention if symptoms occur. Wash clothing before reuse.

**INGESTION:** If swallowed, call a physician immediately. Do NOT induce vomiting. Provided the patient is conscious, wash out mouth with water. Never give anything by mouth to an unconscious person.

**INHALATION:** Remove patient from exposure, keep warm and at rest. Obtain immediate medical attention. Treatment is symptomatic for primary irritation or bronchospasm. If breathing is labored, oxygen should be administered by qualified personnel. Apply artificial respiration if breathing has ceased or shows signs of failing.

**NOTES TO PHYSICIAN:** Symptomatic and supportive therapy as needed. Following severe exposure medical follow-up should be monitored for at least 48 hours.

## 5. FIRE FIGHTING MEASURES

**FLASHPOINT AND METHOD:** 110°C (230°F) Pensky-Martens CC

**EXTINGUISHING MEDIA:** Water spray, carbon dioxide, dry chemical, or alcohol foam.

**EXPLOSION HAZARDS:** Avoid contact with strong oxidizers and strong acids, as sudden reaction may result in fire and toxic fumes. Reacts slowly with water to produce carbon dioxide which may rupture closed containers. This reaction accelerates at higher temperatures.

**FIRE FIGHTING PROCEDURES:** Cool fire exposed containers with water spray. Remove containers from the fire area if possible. Do not release runoff from fire control methods to sewers or waterways.

**FIRE FIGHTING EQUIPMENT:** Firefighters should wear positive pressure self-contained breathing apparatus (SCBA) and consider use of unmanned hose holders or monitor nozzles for fighting large fires.

## 6. ACCIDENTAL RELEASE MEASURES

**SMALL SPILL:** Evacuate the area. Clean-up should only be performed by trained personnel. People dealing with a major spill should wear full protective clothing including appropriate respiratory protection. Prevent product spill from entering sewers or waterways. Neutralize small spills with a decontaminant.

**LARGE SPILL:** Contain and absorb large spills onto an inert, non-flammable adsorbent carrier (such as earth or sand). Shovel into open-top drums or plastic bags for further decontamination, if necessary. Wash the spill area clean with a liquid decontaminant. Remove and properly dispose of residues. Notify applicable government authorities if release is reportable. (See CERCLA in Section 15).

**RELEASE NOTES:** US regulations require reporting spills of this material that could reach any surface waters. The toll free number for the US Coast Guard National Response Center is (800) 424-8802.

## 7. HANDLING AND STORAGE

**GENERAL PROCEDURES:** Avoid contact with eyes, skin and clothing. Use only with adequate ventilation. Avoid breathing vapor over open containers. Avoid open container exposure to damp air. Avoid breathing aerosols, mists, and vapors.

**HANDLING:** Use appropriate personal protective equipment as specified in Section 8. Handle in a well ventilated area. Handle and use in a manner consistent with good industrial/manufacturing techniques and practices.

**STORAGE:** Store in a cool, dry place, away from excessive heat, in original or similar container. Avoid unnecessary contact. Protect from freezing. Containers should be tightly sealed to prevent contamination with foreign materials.

**SHELF LIFE:** 6 months from date of shipment under manufacturers recommended storage conditions.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

**EXPOSURE GUIDELINES:**

## OSHA HAZARDOUS COMPONENTS (29 CFR1910.1200)

<u>Chemical Name</u>	<u>OSHA PEL</u>		<u>ACGIH TLV</u>		<u>SupplierOEL</u>	
	<u>ppm</u>	<u>mg/m<sup>3</sup></u>	<u>ppm</u>	<u>mg/m<sup>3</sup></u>	<u>ppm</u>	<u>mg/m<sup>3</sup></u>
Polytetramethylene glycol polymer 1,3 diisocyanatomethylbenzene terminated	TWA -	NE	NE	NE	NE	NE
	STEL -	NE	NE	NE	NE	NE
Polypropylene glycol polymer 1,3 diisocyanatomethylbenzene terminated	TWA -	NE	NE	NE	NE	NE
	STEL -	NE	NE	NE	NE	NE
Chlorinated paraffins	TWA -	NE	NE	NE	NE	NE
	STEL -	NE	NE	NE	NE	NE
Dibutyl phthalate	TWA -	NE	5	NE	5	NE <sup>[1]</sup> 5 <sup>[1]</sup>
	STEL -	NE	NE	NE	NE	NE
Aromatic hydrocarbon	TWA -	NE	NE	NE	17	100
	STEL -	NE	NE	NE	NE	NE
Naphthalene	TWA -	10	50	10	52	10 <sup>[1]</sup> 50 <sup>[1]</sup>
	STEL -	NE	NE	15	79	15 75
Toluene-2,6-diisocyanate	TWA -	0.02	NE	0.005	NE	NE
	STEL -	NE	NE	NE	0.02	NE
Toluene-2,4-diisocyanate	TWA -	0.02	0.14	NE	NE	NE
	STEL -	NE	NE	NE	NE	NE

## OSHA TABLE COMMENTS:

1. NIOSH REL

## PERSONAL PROTECTIVE EQUIPMENT

**EYES AND FACE:** Safety goggles or glasses are recommended. Plastic face shields should be used for complete face protection to protect against possible splashing or spraying of material. ANSI Z87.1 or approved equivalent.

**SKIN:** Impermeable gloves. Employees should wash their hands and face before eating, drinking, or using tobacco products.

**RESPIRATORY:** Exhaust ventilation recommended. An organic vapor cartridge or fresh air supplied respirator (NIOSH approved) may be necessary for certain applications. Consider the type of application, environmental concentrations, and other materials being used concurrently when determining respirator use and selection. Observe OSHA regulations for respirator use (29 CFR 1910.134).

**PROTECTIVE CLOTHING:** Protective clothing should be selected and used in accordance with 'Guidelines for the Selection of Chemical Protective Clothing' published by ACGIH.

**OTHER USE PRECAUTIONS:** Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower. Training is important. Follow all label precautions.

<b>9. PHYSICAL AND CHEMICAL PROPERTIES</b>
--------------------------------------------

**PHYSICAL STATE:** Viscous liquid

**ODOR:** Slight aromatic hydrocarbon

**APPEARANCE:** Clear

**COLOR:** Pale yellow

**pH:** Not Applicable

**PERCENT VOLATILE:** 2.2

**VAPOR PRESSURE:** < 1 mmHg at 21°C (70°F)

**VAPOR DENSITY:** Not Established

**BOILING POINT:** > 250°C (482°F)

**SOLUBILITY IN WATER:** Reacts slightly with water

**SPECIFIC GRAVITY:** 1.090 (water=1) at 25°C (77°F)

**VISCOSITY #1:** 6000 Centipoise at 25°C (77°F)

**VOC (Volatile Organic Compound):** < 24.000 g/l Reference EPA Method 24

## 10. STABILITY AND REACTIVITY

**STABILITY:** This product is stable under normal ambient conditions of temperature and pressure.

**POLYMERIZATION:** Product may foam when exposed to heat and moisture.

**CONDITIONS TO AVOID:** High temperatures, moisture, and freezing conditions.

**HAZARDOUS DECOMPOSITION PRODUCTS:** Carbon monoxide, carbon dioxide, nitrous oxide, and HCN.

**INCOMPATIBLE MATERIALS:** Moisture, strong acids, amines, and metal carboxylates.

## 11. TOXICOLOGICAL INFORMATION

### TOXICITY TO ANIMALS

Chemical Name	ORAL LD <sub>50</sub> (rat)	DERMAL LD <sub>50</sub> (rabbit)	INHALATION LC <sub>50</sub> (rat)
Polytetramethylene glycol polymer 1,3 diisocyanatomethylbenzene terminated	Not Established	Not Established	Not Established
Polypropylene glycol polymer 1,3 diisocyanatomethylbenzene terminated	Not Established	Not Established	Not Established
Chlorinated paraffins	Not Established	Not Established	Not Established
Dibutyl phthalate	20000 to 25000 mg/kg	> 20960 mg/kg	Not Established
Aromatic hydrocarbon	Not Established	Not Established	Not Established
Naphthalene	490 mg/kg	> 20 g/kg	Not Established
Toluene-2,6-diisocyanate	Not Established	Not Established	Not Established
Toluene-2,4-diisocyanate	5800 mg/kg	Not Established	Not Established

## 12. ECOLOGICAL INFORMATION

**ECOTOXICOLOGICAL INFORMATION:** No specific ecological data are available for this product. Refer to Section 6 for information regarding accidental release and Section 15 for regulatory reporting information.

## 13. DISPOSAL CONSIDERATIONS

**DISPOSAL METHOD:** The generation of waste should be avoided or minimized wherever possible. Disposal should be in accordance with local, state, provincial or national regulations.

**EMPTY CONTAINER:** Containers must be emptied (as defined by RCRA, Section 261.7 or state regulation that may be more stringent) and either passed to an approved recycler or destroyed.

## 14. TRANSPORT INFORMATION

### DOT (DEPARTMENT OF TRANSPORTATION) LAND

**PROPER SHIPPING NAME:** Environmentally hazardous substances, liquid, n.o.s. (See Note)

**TECHNICAL NAME:** (dibutyl phthalate)

**PRIMARY HAZARD CLASS/DIVISION:** 9

**UN/NA NUMBER:** UN 3082

**PACKING GROUP: III****REPORTABLE QUANTITY (RQ) UNDER CERCLA:** 10 lb of dibutyl phthalate**LABEL:** Class 9 (miscellaneous hazardous materials)**NOTE:** Applies ONLY to containers with a RQ of dibutyl phthalate (10 lb), otherwise not regulated.**AIR (ICAO/IATA)****SHIPPING NAME:** Environmentally hazardous substances, liquid, n.o.s. (**See Note**)**TECHNICAL NAME:** (dibutyl phthalate)**UN/NA NUMBER:** UN 3082**PRIMARY HAZARD CLASS/DIVISION:** 9**PACKING GROUP:** III**LABEL:** Class 9 (miscellaneous hazardous materials)**NOTE:** Applies ONLY to containers with a RQ of dibutyl phthalate (10 lb), otherwise not regulated.**VESSEL (IMO/IMDG)****SHIPPING NAME:** Environmentally hazardous substance, liquid, n.o.s.**TECHNICAL NAME:** (dibutyl phthalate)**PRIMARY HAZARD CLASS/DIVISION:** 9**PACKING GROUP:** III**LIMITED QUANTITY:** 5 liters**MARINE POLLUTANT #1:** Yes (dibutyl phthalate)**LABEL:** Class 9 (miscellaneous hazardous materials)**15. REGULATORY INFORMATION****UNITED STATES****SARA TITLE III (SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT)****311/312 HAZARD CATEGORIES:** None**313 REPORTABLE INGREDIENTS:** This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and CFR Part 372:**EPCRA SECTION 313 SUPPLIER NOTIFICATION**

Chemical Name	Wt. %	CAS	Comments
Dibutyl phthalate	1 - 5	000084-74-2	
Naphthalene	< 0.2	000091-20-3	

**CERCLA (COMPREHENSIVE RESPONSE, COMPENSATION, AND LIABILITY ACT)****CERCLA REGULATORY:** For this/these chemicals, release of more than the Reportable Quantity to the environment in a 24-hour period requires notification to the National Response Center (800-424-8802 or 202-426-2675).

Chemical Name	Wt. %	CERCLA RQ
Dibutyl phthalate	1 - 5	10 lb
Naphthalene	< 0.2	100 lb
Toluene-2,6-diisocyanate	< 0.035	100 lb
Toluene-2,4-diisocyanate	< 0.03	100 lb

**TSCA (TOXIC SUBSTANCE CONTROL ACT)****TSCA REGULATORY:** This product contains naphthalene which is subject to TSCA Section 12(b) export notification.**TSCA STATUS:** This product or its components are listed in or exempt from the TSCA inventory requirements.**OCCUPATIONAL SAFETY AND HEALTH ADMINISTRATION (OSHA)****29 CFR1910.119---PROCESS SAFETY MANAGEMENT OF HIGHLY HAZARDOUS CHEMICALS:** None of the chemicals in this product are considered highly hazardous by OSHA.**REGULATIONS**

**STATE REGULATIONS** California Proposition 65: This product contains chemical(s) which are known to the State of California to cause cancer, birth defects or other reproductive harm, and may be subject to the requirements of California Proposition 65 (CA Health & Safety Code Section 25249.5):

**CALIFORNIA PROPOSITION 65**

Chemical Name	Wt. %	Listed
Dibutyl phthalate	1 - 5	<ul style="list-style-type: none"> <li>● Developmental Toxicity</li> <li>● Female Reproductive</li> <li>● Male Reproductive</li> </ul>
Naphthalene	< 0.2	● Cancer
Toluene-2,6-diisocyanate	< 0.035	● Cancer
Toluene-2,4-diisocyanate	< 0.03	● Cancer

**OSHA HAZARD COMM. RULE:** The contents of the MSDS comply with the OSHA Hazard Communication Standard 29 CFR 1910.1200.

**16. OTHER INFORMATION**

**REASON FOR ISSUE:** Revised format


**APPROVED BY:** Michael Rose    **TITLE:** R & D Manager

**PREPARED BY:** Gus Alidad

**REVISION SUMMARY:** New MSDS

**HMIS RATING**

<b>HEALTH:</b>	<input type="checkbox"/>	<b>1</b>
<b>FLAMMABILITY:</b>		<b>1</b>
<b>PHYSICAL HAZARD:</b>		<b>1</b>
<b>PERSONAL PROTECTION:</b>	<b>X</b>	

**NFPA CODES**

**HMIS RATINGS NOTES:** Personal Protection: See Section 8

**MANUFACTURER DISCLAIMER:** This information is furnished without warranty, expressed or implied, except that is accurate to the best knowledge of BJB Enterprises, Inc. The data on this sheet relates only to the specific material designated herein. BJB Enterprises, Inc. assumes no legal responsibility for use or reliance upon this data.