



SC-89 THINNER FOR REDUCING SC-89 PAINT

DESCRIPTION:

SC-89 Thinner has been reformulated to incorporate the use of safer solvents.* This thinner is recommended for use with BJB's SC-89 series paints. It may also be used as a part cleaner prior to painting.

USAGE:

When thinning the SC-89 paint for spraying, use 2 1/2 - 3 parts thinner to one part paint. This dilution ratio will eliminate the "cob-webbing" often observed during spraying. When brushing SC-89 paint, generally a one to one dilution is adequate.

STORAGE:

Store at room temperature in a dry area. Unopened containers will have a shelf life of six months from date of shipment when properly stored under normal conditions at 77° F (25° C).

PACKAGING:

5-Gallon pails34 lbs.

SAFETY PRECAUTIONS:

Use in a well-ventilated area. Avoid contact with skin using protective gloves and protective clothing. Repeated or prolonged contact on the skin may cause an allergic reaction. Eye protection is extremely important. Always use approved safety glasses or goggles when handling this product.

IF CONTACT OCCURS:

Skin: Immediately wash with soap and water. Remove contaminated clothing and launder before reuse. Seek qualified medical attention if allergic reactions occur.

Eyes: Immediately flush with water for at least 15 minutes. Call a physician.

Ingestion: If swallowed, call a physician immediately. Remove stomach contents by gastric suction or induce vomiting only as directed by medical personnel. Never give anything by mouth to an unconscious person.

Refer to the Material Safety Data Sheet before using this product.

* SC-89 Thinner now conforms to the EPA's new Clean Air Act, Section 112 and the voluntary 33-50 program. It contains no hazardous air pollutants (HAP's) per 40 CFR part 61; and contains no ozone depleting chemicals (ODC's) per 40 CFR part 82.