

Material Safety Data Sheet

TC-1622 PART B

Date of Preparation: 02/15/2002

Revision: 02/15/2002

Section 1 - Chemical Product and Company Identification

Product Name: TC-1622 PART B

Product Class: Epoxy hardener

Chemical Type: Aliphatic, cycloaliphatic amine mixture

Manufacturer: BJB Enterprises, Inc., 14791 Franklin Avenue, Tustin, CA 92780, Phone (714) 734-8450, Fax (714) 734-8929, (M-Th: 8-4:30, F: 7:30-4), Emergency Phone: Chemtrec (800) 424-9300 or (703) 527-3887

Section 2 - Composition / Information on Ingredients

Ingredient Name	CASRN	% wt
1. Tetraethylenepentamine (TEPA)	112-57-2	<50
2. Diethylenetriamine (DETA)	111-40-0	<10

Trace Impurities: N/A

Ingredient	OSHA PEL		ACGIH TLV		NIOSH REL		NIOSH IDLH
	TWA	STEL	TWA	STEL	TWA	STEL	
#1	NE	NE	NE	NE	NE	NE	NE
#2	1.000 ppm	NE	1.000 ppm	NE	NE	NE	NE

Section 3 - Hazards Identification

☆☆☆☆☆ Emergency Overview ☆☆☆☆☆

Appearance: Liquid; Odor: Ammoniacal; Avoid skin contact. Avoid breathing vapors. May cause eye and skin irritation. Harmful if inhaled. Use in well-ventilated areas. Decomposition and combustion products are toxic.

HMIS

H 3

F 1

R 0

PPE†

†Sec. 8

Potential Health Effects

Primary Entry Routes: Eye and skin contact; inhalation of vapors, accidental ingestion.

Inhalation/Ingestion: Excessive vapors caused by heat or spray mist can cause respiratory problems.

Eye: May cause irritation or possible burns.

Skin: May cause irritation and possible allergic sensitivity with repeated contact.

Medical Conditions Aggravated by Long-Term Exposure: Acute asthma or prior sensitization to amine fumes.

Section 4 - First Aid Measures

Inhalation: Not likely. Remove to fresh air environment.

Ingestion: If swallowed, call a physician immediately. Remove stomach contents by gastric suction or induce vomiting only as directed by medical personnel. Never give anything by mouth to an unconscious person.

Eye Contact: Flush eyes with clean, lukewarm water for 15 minutes. Obtain medical attention if irritation develops.

Skin Contact: Remove contaminated clothing and wash affected areas well with soap and water. Launder contaminated clothing before use.

Note to Physicians: Treat any ill effects symptomatically.

Section 5 - Fire-Fighting Measures

Flash Point/Method: 225°F (107°C) Tag closed cup

Extinguishing Media: Carbon dioxide, dry chemical, foam or water spray.


Hazardous Classification: Class 8, PG III

Unusual Fire or Explosion Hazards: Decomposition and combustion products are toxic.

Fire-Fighting Instructions: Cool fire exposed containers with water spray. Remove containers from fire area if possible. Do not release runoff from fire control methods to sewers or waterways.

Fire-Fighting Equipment: Firefighters must wear positive pressure self-contained breathing apparatus (SCBA) for fighting large fires. Consider the use of unmanned hose holders or monitor nozzles when fighting large fires.

NFPA



Section 6 - Accidental Release Measures

Spill /Leak Procedures: Provide adequate ventilation and wear personal protective equipment. Evacuate personnel as a precaution. Prevent product spill from entering sewers, streams, or drinking water supplies. Collect liquid or soak up with inert filler or an absorbent such as dry earth, sand or oil absorbent (sweeping) compound. Collect liquid into suitable containers for disposal. Wash area with dilute ammonia solution.

Containment: For large spills, dike ahead of liquid spill for later neutralization, absorption, clean up, and disposal.

Section 7 - Handling and Storage

Handling Precautions: Corrosive; causes eye and skin burns. Avoid contact with eyes, skin and clothing. Avoid breathing vapor directly over open container.

Storage Requirements: Store in a cool, dry place away from excessive heat in original or similar waterproof containers. Avoid unnecessary contact. Protect from freezing. Containers should be tightly sealed to prevent contamination with foreign materials.

Shelf life: 12 months, from date of shipment, under manufacturers recommended storage conditions.

Section 8 - Exposure Controls / Personal Protection

Eye Protection Requirements: Safety goggles or glasses are recommended. Plastic face shield should be worn for complete face protection.

Skin Protection Requirements: Impermeable gloves should be worn. Employees should wash their hands and face before eating, drinking, or using tobacco products.

Ventilation/Respiratory Requirements: Exhaust ventilation recommended. An organic vapor cartridge or fresh air supplied respirator may be necessary for certain applications. Consider the type of application, environmental concentrations, and other materials being used concurrently when determining respirator use and selection. Observe OSHA regulations for respirator use (29 CFR 1910.134).

Additional Protective Measures: Safety showers and eye wash stations should be easily accessible to the work area. Working training is important. Follow all label precautions.

Section 9 - Physical and Chemical Properties

Physical State: Liquid

Odor: Ammoniacal

Vapor Pressure: Nil at 1 ATM

Specific Gravity (H₂O=1): 0.98

pH: N/A

Water Solubility: Moderate

Boiling Point: >400°F (204°C)

Viscosity: 250 cps

% Volatile: <1

V.O.C. (ref EPA meth 24): <10 gm/liter

Section 10 - Stability and Reactivity

Stability: TC-1622 PART B is stable at room temperature in closed containers under normal storage and handling conditions.

Polymerization: Hazardous polymerization will not occur.

Chemical Incompatibilities/Conditions to Avoid: Strong oxidizers and acids.

Hazardous Decomposition: Decomposition and combustion products are toxic.

Section 11- Toxicological Information

No Toxicological Information Available

Section 12 - Ecological Information

No Ecological Information Available

Section 13 - Disposal Considerations

Waste Disposal Method: Controlled incineration or landfill burial unless prohibited. Dispose of in compliance with federal, state, or local environmental control regulations.

Section 14 - Transport Information

DOT Shipping Name: Corrosive liquid, n.o.s.	DOT (USA): Regulated
Technical Name: (tetraethylenepentamine solution)	Class 8, PG III
Hazard Class: Class 8	IATA/ICAO: Regulated
ID No.: UN 1760	Class 8, PG III
Packing Group: III	IMO/IMDG: Regulated
Label: Corrosive	Class 8, PG III

Section 15 - Regulatory Information**U.S. Federal Regulations:****OSHA:**

This document has been prepared in accordance with the MSDS requirements of the OSHA Hazard Communication Standard.

SARA TITLE III:

Sections 311/312 Hazard Classification:

None

Section 313: This product contains the following substances subject to the reporting requirements of EPCRA, Section 313 and 40 CFR Part 372:

None

TSCA: This product or its components are listed in or exempt from the TSCA inventory requirements.

This product contains the following substances subject to export notification under Section 12 (b) of TSCA:

None

Section 16 - Other Information

Reason for Issue: New Issue

Prepared By: S.F. Marks

Approval Date: 02/15/2002

Supersedes Date: N/A

Disclaimer: This information is furnished without warranty, expressed or implied, except that it is accurate to the best knowledge of BJB Enterprises, Inc. The data on this sheet relates only to the specific material designated herein. BJB Enterprises, Inc. assumes no legal responsibility for use or reliance upon these data.